

IBM System Storage TS1120 Tape Drive



Overview

The IBM System Storage™ TS1120 Tape Drive (TS1120 tape drive) offers a solution to address applications that need high capacity, fast access to data or long-term data retention. It is supported in IBM tape libraries, IBM frames that support stand-alone installation, and in an IBM 3592 Tape Frame Model C20 (3592 C20 frame) attached to a Sun StorageTek™ 9310 library.

Highlights

- **Supports IBM Systems and selected open system platforms**
- **Supported on existing IBM and Sun StorageTek automation**
- **Offers native data transfer rate of up to 104 MBps**
- **Supports 3592 fast access, standard capacity and extended capacity cartridges**
- **Supports data encryption and key management**

The tape drive uses IBM 3592 Cartridges, which are available in limited capacity (100GB) for fast access to data, and standard capacity (500 GB) or extended capacity (700 GB) that help to reduce resources to lower total cost. All three cartridges are available in re-writable or Write Once Read Many (WORM) format.

TS1120 tape drives can be shared among supported open system hosts on a Storage Area Network (SAN) or

between IBM FICON® and ESCON® mainframe hosts when attached to an IBM System Storage TS1120 Tape Controller (TS1120 tape controller). Sharing drives optimizes drive utilization and helps reduce infrastructure requirements.

High performance

The TS1120 tape drive supports a native data transfer rate of up to 104 MBps. In open system environments where data typically compresses at 2:1, the TS1120 tape drive can transfer data up to 200 MBps. In a mainframe environment where data typically compresses at 3:1, a single tape drive can transfer data up to 260 MBps. This can help reduce backup and recovery times or require fewer resources to support the environment.

Flexible usage

As the TS1120 tape drive addresses applications that need high capacity as well as applications that require fast access to data, it can eliminate the necessity to purchase two different tape drives. Additionally, the TS1120 tape drive can use 3592 WORM cartridges that are designed to help support data retention needs and are also able to read and write 3592 re-writable

cartridges in the same format as the previous IBM TotalStorage® 3592 Model J1A tape drive to facilitate interchange.

Investment protection

The TS1120 tape drive helps protect existing investments in tape automation by offering compatibility with existing automation. The TS1120 tape drive is supported in IBM System Storage TS3400 and TS3500 Tape Libraries (TS3400 tape library, TS3500 tape library) or the IBM TotalStorage 3494 Tape Library and can attach to IBM Virtualization Engine TS7700 or IBM Virtual Tape Server models. The TS1120 tape drive is also supported in the IBM 3592 C20 frame for attachment to the Sun StorageTek 9310 silo where it can co-exist with supported IBM and Sun StorageTek tape drives.

Encryption Support

Increasing attention is being paid to the need to protect company data against theft or accidental loss, particularly data that contain personal or sensitive information of a company's customers. The TS1120 now includes data encryption capabilities within the drive itself, helping to avoid the need for host-based

encryption of data—and the concurrent drain on host performance—or the use of specialized encryption appliances. This capability is intended to provide customers with greater ability to protect information if tape cartridges are lost or stolen by supporting the storage of the data in an encrypted form.

The IBM Encryption Key Manager component for the Java™ platform can help generate and manage encryption keys for TS1120 tape drives across the enterprise. This feature uses standard key repositories on supported platforms and supports three different encryption management methods: application managed, system managed, or library managed. The TS1120 tape drive supports transparent encryption, minimizing application changes in the system and library managed implementations. The TS1120 tape drive encryption capability is designed to avoid the need for application changes in the system and library managed implementations. The encryption capability is supported when the TS1120 tape drive is integrated into or attached to the TS3400 tape library, the TS3500 tape library, the TS1120 tape controller, the 3494 tape library, the IBM 3592 C20 frame or is used in stand-alone environments.

Multiplatform support

To support a heterogeneous server environment, the TS1120 tape drive is supported on IBM System p™, System i™¹ and System x™ and supported on System z™ servers by the TS1120 tape controller.

The TS1120 tape controller is designed to offer ESCON and FICON attachment of either TS1120 or 3592 J1A tape drives in a 3494 or TS3500 tape library, 3592 C20 frame or standalone rack or frame. To support TS1120 or 3592J1A tape drives in a TS3500 Tape Library, the TS1120 tape controller must be installed in an IBM 3953 Tape Frame Model F05. To support drives in a 3494 tape library and 3592 C20 frames, the TS1120 tape controller must reside in an IBM 3952 Tape Frame Model F05.

Tape drives can be shared by FICON and ESCON hosts, which may help reduce hardware and infrastructure requirements. The TS1120 tape controller also offers the ability to perform non-disruptive addition of tape drives, which helps enhance configuration flexibility and availability.

Further information on supported environments can be found in the specifications in this document or at the following URL:

ibm.com/storage/tape/ts1120

Application support

IBM Tivoli® Storage Manager and other compatible software offerings provide storage and tape management software that supports the TS1120 tape drive. Supported software and applications should be obtained separately from IBM, IBM Business Partners, or independent software vendors (ISVs). For a list of compatible software and additional information, refer to the TS1120 tape drive ISV Matrix at the following Web site:

ibm.com/storage/tape/ts1120

Advanced technology

The TS1120 tape drive is designed to help protect mission-critical data and incorporates error correction code and factory written servo tracks on the tape cartridge for precise head positioning. In addition, unique functions such as

virtual backhitch and a high resolution directory are designed to improve access to data and reduce wear and tear on the media respectively.

3592 media

The TS1120 tape drive requires the use of the IBM 3592 cartridge. Cartridges are available in short, standard and extended lengths and in re-writable and WORM formats. Cartridges can be ordered in packs of 20 and can be labeled and initialized, initialized only, or unlabeled and uninitialized. For more information, contact your IBM representative or IBM Business Partner or visit:

ibm.com/storage/media

Competitive financing options

IBM Global Financing offers some of the industry's most competitive rates for a wide range of IBM products and services, including the TS1120 tape drive, for the duration of the financing term. For more information, please visit:

ibm.com/financing

TS1120 tape drive at a glance

Characteristics

Recording technique	Linear Serpentine
Number of tracks	896
Native capacity	700 GB (using JB/JX media), 3003/500 GB (using JA/JW media) or 60 ³ /100 GB (using JJ/JR media)
Native data rate	104 MBps
Adaptive data rates	104, 85, 70, 55, 41 and 35 MBps for 3592 cartridges initialized in Gen 2 format 54, 41, 36, 31 and 27 MBps for 3592 cartridges initialized in Gen 1 format
Burst data rate	400 MBps
High-speed search	10 mps
Warranty	One year

Physical characteristics

Dimensions	95 mm H x 198 mm W x 467 mm D (3.8 in x 7.8 in x 18.4 in)
Weight	5.7 kg (12 lbs 7 oz)

Operating environment

Temperature with media	16° to 32° C (60° to 90° F)
Relative humidity	20% to 80% non-condensing (limited by media)
Wet bulb maximum	26° C (78.8° F)
Heat output	307 BTU/hr
Power requirements	0.1 kVA

Platform Support

	Platform	Operating System
IBM	System p System i System x System z	IBM AIX® and SUSE Enterprise Server IBM i5/OS® ¹ and IBM OS/400® ¹ see open system support IBM z/OS®, IBM z/VM®, IBM VSE/ESA™ and SUSE Enterprise Server
Open Systems	Hewlett-Packard Sun Microsystems Servers with Intel® or AMD processors	HP-UX Solaris SUSE Linux® Red Hat Microsoft® Windows® 2000, Windows NT®, Windows Server® 2003
Encryption support		z/OS, z/VM, i5/OS, AIX, HP, Sun, Linux and Windows

TS1120 Tape Controller at a glance

Characteristics

Number of ESCON interfaces	up to 8
Number of FICON interfaces	up to 4
ESCON maximum channel link speed	17 MBps
FICON maximum channel link speed	400 MBps
ESCON maximum distance (unrepeated, single link to controller)	3 km
FICON long wavelength maximum distance (unrepeated, single link to controller)	100 km
FICON short wavelength maximum distance (unrepeated, single link to controller)	150 m
Warranty	1 year

Physical characteristics

Dimensions	172 mm H x 442 mm W x 573 mm D (6.8 in H x 17.4 in W x 22.6 in D)
Weight	35 kg (78 lb)

Operating environment

Temperature (with media)	16° to 32° C (60° to 90° F)
Relative humidity	20% to 80% non-condensing (limited by media)
Wet bulb maximum	23° C (73.4° F)
Heat output	2.05 BTU/hr
Power requirements	600 Watts

3952 F05 frame at a glance

Number of controllers	Up to three TS1120 controllers
------------------------------	--------------------------------

Physical characteristics

Dimensions	1804 mm H x 644 mm W x 1102 mm D (71.0 in H x 25.4 in W x 43.2 in D)
Weight	279.5 kg (616 lbs)

Operating environment

Temperature	50° F to 90° F (10° C to 32° C)
Relative humidity	20% to 80%
Wet bulb maximum	23° C (73.4° F)
Heat output	1190 Watts ²
Power requirement	2046 BTU/hr ²

3592 C20 frame at a glance

Number of drives Up to twenty TS1120 or 3592 Model J1A drives

Physical characteristics

Dimensions 1803 mm H x 724 mm W x 775 mm D (71.0 in H x 28.5 in W x 30.5 in D)
Weight 407 kg (896 lbs)

Operating environment

Temperature 60° F to 90° F (16° C to 32° C) media limited
Relative humidity 20% to 80% limited by media
Wet bulb maximum 23° C (73.4° F)
Heat output 5.1 kBTU/hr²
Power requirement 1.5 kVA²

For more information

Contact your IBM representative or IBM Business Partner or visit:

ibm.com/storage/tape



© Copyright IBM Corporation 2007

IBM Systems and Technology Group
Route 100
Somers, New York 10589
U.S.A.

Produced in the United States of America
July 2007
All Rights Reserved

IBM, the IBM logo, the e-business logo, AIX, ESCON, FICON, i5/OS, OS/400, S/390, System i, System p, System x, System z, System Storage, Tivoli, TotalStorage, VM/ESA, VSE/ESA, z/OS and z/VM are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries or both.

Microsoft, Windows, Windows NT, Windows Server and the Windows logo are registered trademarks of Microsoft Corporation in the United States, other countries or both.

Intel, Intel Inside (logos), MMX and Pentium are trademarks of Intel Corporation in the United States, other countries or both.

Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc., in the United States, other countries or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.

This document could include technical inaccuracies or typographical errors. IBM may make changes, improvements or alterations to the products, programs and services described in this document, including termination of such products, programs and services, at any time and without notice. Any statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only. The information contained in this document is current as of the initial date of publication only and is subject to change without notice. IBM shall have no responsibility to update such information.

IBM is not responsible for the performance or interoperability of any non-IBM products discussed herein. Performance data for IBM and non-IBM products and services contained in this document was derived under specific operating and environmental conditions. The actual results obtained by any party implementing such products or services will depend on a large number of factors specific to such party's operating environment and may vary significantly. IBM makes no representation that these results can be expected or obtained in any implementation of any such products or services.

MB, GB and TB equal 1,000,000, 1,000,000,000 and 1,000,000,000,000 bytes, respectively, where referring to storage capacity. Actual storage capacity will vary based upon many factors and may be less than stated. Some numbers given for storage capacities give capacity in native mode followed by capacity using data compression technology.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS-IS" WITHOUT ANY WARRANTY, EITHER EXPRESSED OR IMPLIED. IBM EXPRESSLY DISCLAIMS ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements (e.g., IBM Customer Agreement, Statement of Limited Warranty, International Program License Agreement, etc.) under which they are provided.

References in this document to IBM products, programs or services does not imply that IBM intends to make such products, programs or services available in all countries in which IBM operates or does business. Any reference to an IBM program or product in this document is not intended to state or imply that only that program may be used. Any functionally equivalent program or product that does not infringe IBM's intellectual property rights may be used instead. It is the user's responsibility to evaluate and verify the operation of any non-IBM product, program or service.

¹ Assumes 3:1 compression

¹ WORM support not available.

² Assumes 110V power.

³ Assumes Gen 1 format.